

Race time / Lap: _____

Best lap: _____

Name: _____
Date: _____
Track: _____

Diff. Oil

Front: _____
Center: _____
Rear: _____

Track Conditions

Size: ☐ Open ☐ Med. ☐ Tight
Traction: ☐ High ☐ Med. ☐ Low
Surface: ☐ Smooth ☐ Med. ☐ Bumpy

Tire

Front Type: _____ Rear Type: _____
Foam: _____ Foam: _____

Electric System

ESC Type: _____
Motor Type: _____
Motor Gear/Spur Gear: _____

Front Suspension

Camber: _____ mm ()°

□ 4.7mm
□ 5.7mm
□ 6.7mm
□ 7.7mm

R: _____ mm
F: _____ mm

Front lower arm
☐ Pro-composite
☐ Hard Material ☐ Standard Material

Front Toe-In

F: ☐ 0.5 ☐ 1.0
R: ☐ 0.5 ☐ 1.0

C-Hub ☐ 9 ☐ 11

Steering Ackerman

□ 1
□ 2
□ 3

Diff. Position

Front	0 ☐	1 ☐	2 ☐	3 ☐
Rear	0 ☐	1 ☐	2 ☐	3 ☐

Oil: _____
Spacer: _____ mm
Pistons: _____
Spring: _____

Track width _____ mm
Camber angle _____
Toe angle _____
Rebound stop _____ mm
Sway bar ☐ Use _____ mm
☐ None
Ride High: _____ mm

Rear Suspension

Camber: _____ mm ()°

□ 4.7mm
□ 5.7mm
□ 6.7mm
□ 7.7mm

Rear lower arm
☐ Pro-composite
☐ Hard Material ☐ Standard Material

Wing Angle

□ 0 □ +3 □ -3

Front insert ☐ H ☐ M ☐ L
Wing Position ☐ H ☐ M ☐ L

Body: _____
Rear Wing: _____
Front Wing: _____

Rear Toe-In

F: ☐ 0.5 ☐ 1.0
R: ☐ 0.5 ☐ 1.0

Oil: _____
Spacer: _____ mm
Pistons: _____
Spring: _____

Rear Sway bar ☐ Use _____ mm
☐ None
Ride High: _____ mm

Option Parts List

Side guard

☐ Pro-composite
☐ Hard Material ☐ Standard Material

Carbon Center T-brace

☐ Use
☐ None

T-bar

Front ☐ Pro-composite
☐ Hard Material ☐ Standard Material
Rear ☐ Pro-composite
☐ Hard Material ☐ Standard Material